

# TANDEM AXLE JEEP

MODEL: LPJ-40T-2



# **TRAILER FEATURES**

#### SINGLE DROP **PROFILE**

Designed with a low 5th wheel height to maintain a low center of gravity.

SLIDING FIFTH

Multiple positions over

a 60" slide range allows

accommodating weight

WHEEL

for flexibility in

equalization.









# **THROAT**





# NARROW PICK-UP

CENTERLINE


The pick-up throat allows easy connection to the jeep.

#### REAR SKID RAMPS

The rear tail frame is designed for use with all types of lowbed trailers.

#### ALUMINUM **FENDERS**

Aluminum checker fenders on gooseneck provide protection for the trailer and the cargo loaded on the trailer.



# **SPECIFICATIONS**

| MODEL        | LPJ-40T-2   |
|--------------|---|
| LENGTH       | 26'1'   |
| WIDTH        | 8'6"  |
| KING PIN     | 14" Setting   |
| COUPLER      | 51" Coupler height, 3/8" plate  |
| FRONT        | Narrow steel pick-up throat   |
| LANDING GEAR | (2) speed crank landing legs - crank located on street side                                 |
| FIFTH WHEEL  | 60" manual sliding style fifth wheel  |
| REAR FRAME   | Tapered rear frame and skid ramps   |
| SUSPENSION   | (2) 30,000 lb. air ride suspension at 54" axle spacing                                      |
| AXLES        | (2) 25,000 lb. axles at 77" track (8'6" wide over tires) Stemco HP Seals                    |
| BRAKES       | 16 ½" x 7" brakes c/w auto slack adjusters<br>and parking brakes<br>Meritor/WABCO 2S/1M ABS |
| HUBS & DRUMS | $10 \ \text{stud}$ steel piloted hubs and outboard cast drums                               |

| WHEELS               | 10 stud steel pilot mount 8.25 x 22.5 disc wheels - silver  |
|----------------------|---|
| TIRES                | 275/70R-22.5 low profile radial tires   |
| ELECTRICAL<br>System | LED rubber mounted sealed beam lighting system Integrated wiring harness system                     |
| FENDERS              | Aluminum checker plate on gooseneck   |
| MUDFLAPS             | Heavy duty rubber with anti-sail brackets<br>behind fenders<br>Heavy duty rubber at rear            |
| FINISH               | Sandblasted, primed, and painted with PPG urethane paint  |
| SAFETY TAPE          | Applied as per regulations  |
| WARRANTY             | 1st year - 100% parts & labour<br>2nd year - 50% parts & labour<br>3rd to 5th year - 50% parts only |

### **OPTIONS**

- Available in different frame profiles and lengths
- Tridrive tractor compatible and tridem suspension
- Rear liveroll
- · Telescopic adjustable swing up dolly legs
- Air-Weigh on-board scale system
- Lightweight wheels, hubs, and drums

Product improvement is an ongoing process. The manufacturer reserves the right to change any specifications or components on any or all products without prior notice and is under no obligation to undertake modifications to units manufactured to prior changes in specifications.

